

Z-IP Chassis 10U Product Specifications



Z-IP Chassis 10U

Product Specifications



Input	Blade Mobile	Service Type	Service Density	Supported Input Types				
				Analog	HD/SD-SDI	DVB/ASI	HDMI	IP
	Z-Blade Mobile Enterprise	OTT/Mobile Transcoding	3 x ABR					✓
	Mobile Lite	OTT/Mobile Streaming	10 x HD/SD					✓
	Z-IP StreamC REM	H.264 HD/SD	4 x HD/SD	✓	✓		✓	
<ul style="list-style-type: none"> ⚡ Z-Blade Mobile Enterprise Adaptive Bit Rate may contain up to 8 unique profiles each ⚡ Z-IP StreamC REM blades can be seamlessly upgraded from any configuration to 4 x HD via firmware upgrade 								

Physical and Power	Platform	Z-IP Chassis 10U	Z-IP Chassis 4U	Z-IP Chassis 1U
Streaming Network Ports		2 x 1000BaseT	2 x 1000BaseT	2 x 1000BaseT
Management Network Ports		2 x 1000BaseT	1 x 1000BaseT	1 x 1000Base T
Service Blade Slots		13	6	1
Redundant Controller Set		✓		
Width		19" /48cm	19"/48cm	19"/48cm
Height		10RU	4RU	1RU
Depth		12"/30cm	12"/30cm	12"/30cm
Input Voltage Range		100-240 VAC/DC 36-72 VDC	100-240VAC	100-240VAC
Power Consumption		900W Max	600W max	200W max
Hot Swappable components		Power supplies, system fans, Service Blades, Controller Blade, Switch Blade	Power supplies, system fans, Service Blades	Service Blade

Z-IP Chassis 10U

Product Specifications



Management	Compliance
<ul style="list-style-type: none">SNMP RFC3416 with remote clientTelnet, RS-232N+K supported by Cluster Management	<ul style="list-style-type: none">EN 55022/55024FCC Part 15, Subpart B, Class ACSA/CE, RoHs/WEEE