

# Z-Balun DPX

## Product Specifications



# Z-Balun DPX

## Product Specifications



### Product Description

The *Z-Balun DPX* is one of the essential components of Z-Band's high definition video distribution system. It is located at the receive end of the system and permits a TV, Set Top Box/Cable Box or PC with a Tuner Card to be connected to the system for HDTV over CAT 5e or better cable. The balun is not only an impedance matching device, but serves also as a small self-adjusting amplifier and signal conditioner that senses its distance from the hub, and adjusts its output to assure proper signal level to the TV at distances up to 100 meters. It also enables communications with VOD systems and set top boxes from CATV providers. The input to the *Z-Balun DPX* from a wall outlet is connected via an RJ-45 Jack and its output features an F-Connector and an auxiliary RJ-45 Jack for IP application.

Available in free-hanging configurations; a uni-directional (ZBT0010021) capability for RF video only, or a bi-directional (ZBT0010022) capability for video, data, and VOD applications.

### Features & Benefits

Automatically senses horizontal Category cable distance as shown by LED indicators on free-hanging balun. Adjusts TV receive level by inserting proper signal conditioning algorithm. Provides unique identification impedance signature to *Z-Distribution REG* for port activation. DATA (DOCSIS)/FSK preamble activates the return path.

Part #	ZBT0010022
Physical Description	<b>Weight:</b> Approximately 6 ounces <b>Size:</b> 2.8" L x 2.4" W x 1.0" H F-Connector (bottom) (2) RJ-45 Jacks (top) LED distance indicators (bottom)
Power	8 VDC at ½ watt supplied remotely on RJ 45 pins 7&8 via Z-Distribution REG (no local power required)
Electrical Radio Frequency	Impedance matching 100ohm to 75ohm with signature protection to avoid accidental data connection <b>Forward:</b> 5 MHz to 860 MHz (pins 7 & 8) Assures proper TV receive level 0 to +15 dBmV for analog signals and +/-10 dBmV for digital <b>Return Path:</b> 5 MHz to 42 MHz <b>Return Loss:</b> greater than 14 dB <b>C/N:</b> greater than 43 dB <b>MER:</b> greater than 32 dB

# Z-Balun DPX

## Product Specifications



Return Path	<b>Response Level:</b> 14 dBmV <b>Response Time:</b> 10 micro seconds
Environment	<b>Operating Temperature:</b> 0 to 55° C <b>Relative Humidity:</b> 5 to 95% <b>Storage Temperature:</b> -40 to 70° C
Agency Standards	FCC Part 15, Subpart B Compliant