

# Z-TV Control 232

## Product Specifications



# Z-TV Control 232

## Product Specifications

### Product Description

A fully functional IP-to Z-TV Control 232 Serial Controller (remotely accessed), available in a 24 port configuration. The 1U high rack mounted serial controller utilizes RJ-45 connectors and has one administrator assigned IP address per device. The serial devices (TVs, Set-Top boxes, etc.) are accessed by the LAN input port and controlled by the numbered output ports via the Z-TV Balun 232 . An **external web server** allows IT/AV managers to remotely control every connected TV.

### Features

Each serial controller has only **one** unique IP address and can control up to 24 serial devices. Provides Remote Power to Z-TV Balun 232.

#### Control Systems Functions/Options:

- ✓ Scheduling
- ✓ Turns TVs On and Off
- ✓ Controls Channel Selection
- ✓ Changes Volume Control
- ✓ Devices (Smartphone, Tablet)
- ✓ Controls Selective TV Display Groups or Individual TVs
- ✓ Changes TV Inputs (HDMI, VGA, AUX)
- ✓ Can be Used for Alert Notification
- ✓ Uses Any Network or LAN Mobile

Part #	ZBT0030001
Physical Description	<b>Weight:</b> Approx. 3.5 lbs <b>Dimensions:</b> 19" L x 7" W x 1.75" H Mounts in Standard 19" Rack/1U High
Electrical Power	12V, 1.25A, 82 BTU/HR
Processor	900MIPS
Memory	128MB 500DDR2
LAN	10/100 Ethernet with Auto-MDX
Power Indicator	<b>LED:</b> Green denotes power on

# Z-TV Control 232

## Product Specifications

Set-Up	Built-In Web Pages
Output Control Ports	<b>24 Ports:</b> Baud Rates up to 115KB
Environment	<b>Operating Temperature:</b> 0° to 55° C <b>Relative Humidity:</b> 5 to 95% <b>Storage Temperature:</b> -40° to 70° C
Agency Standards	UL/CSA Listed