



# Z-Distribution ZHC

## Standard

# Product Specifications



# Z-Distribution ZHC Standard Product Specifications



## Product Description

The Z-Distribution ZHC is the 5<sup>th</sup> generation of Z-Band's RF distribution system to implement RF over a category cable. The ZHC is designed to distribute channels 2-135 of an RF video system (54 to 860MHz) while keeping the video programming in its native RF format. The unit automatically splits, amplifies, slopes, and attenuates signal levels when necessary. The system is designed to balance itself with no external amplification or manipulation.

## Options

The Z-Distribution ZHC includes a variety of options for both connections and functionality. The system can support either a coaxial or single-mode fiber signal input. The system can be configured to support 8/16/24 output connections via the front panel's RJ45 interface. Remote system management software is also available. We recommend contacting your Z-Band market manager or territory rep for ordering information and details on option packages.

## Monitoring & Management Software

Z-Band's Z-Distribution ZHC is the first of our systems to offer a full diagnostic and system monitoring software that will be accessible via the network. This software platform allows our customers and authorized technical support personnel to monitor and manage individual units or entire systems. This software will increase our capability to assist with the management and diagnosis of issues with Z-TV deployments and add an additional level of service to Z-Band and its partners.

Models	Z-Distribution ZHC Standard 8/16/24 F/P/X
Physical Description	<b>Dimensions:</b> 17" wide x 1 7/16" high x 12" deep (designed for 1RU of rack space) <b>Weight:</b> 7lbs
Electrical Power	<b>Max Power Consumption:</b> 12V DC @ 8.5A via external power supply (102W MAX) <b>External Power Supply Input Voltage:</b> 100-240V AC, 50-60Hz, 2A Max
Transmission Details	RF Signal outbound on pins 7&8 of CAT cable, Proprietary control data on pins 4&5 and IP data (10/100 maximum) passed on pins 1,2,3,6
LED Lights	Front Panel Only, Listed Top To Bottom <ul style="list-style-type: none"><li>• Master – Red LED, On when unit is in Master Mode</li><li>• Satellite – Yellow LED, On when unit is in Satellite Mode</li><li>• Power – Solid Green LED (flashes when unit detects issues with power supply)</li></ul>

# Z-Distribution ZHC Standard Product Specifications



System Requirements	<ul style="list-style-type: none"> <li>• Coax INPUT: 18-20dBmV RF Power</li> <li>• Fiber INPUT: -2dBm to -3.5dBm @1310nm wavelength</li> <li>• MER (Modulation Error Rate) greater than 40dB</li> </ul>	
Resolution	<p><b>Video Resolution:</b> Z-Band system makes no manipulation to video programming. All RF content is passed through to the viewing/decoding device. This includes, closed captioning, EAS data, alternate languages; all analog or digitally modulated content.</p>	
Supported RF Spectrum	<ul style="list-style-type: none"> <li>• Supports forward path RF frequencies from 48Mhz to 860MHz.</li> <li>• Optional support for reverse path (see Bi-Directional Addendum for more details)</li> <li>• Pilot Tone at 240MHz with power level of 23dBmV on all eight coaxial outbound ports</li> </ul>	
Input/Output	Input	Output
	<ul style="list-style-type: none"> <li>• F-Connector for RG-6 or RG-11 coaxial input (CATV/CASC IN port)</li> <li>• Ethernet 10/100Base-T via RJ-45 shielded connector (Management Port)</li> <li>• Single Mode Fiber w/ SC-APC Connection (SC-APC Fiber Port)</li> </ul>	<ul style="list-style-type: none"> <li>• Qty. 8 Outbound Coaxial F-Connectors on rear panel for distribution of TV Signal to satellite Distribution ZHC units</li> <li>• Qty. 8/16/24 RJ-45 ports on front panel for distribution to Z-TV Baluns.</li> </ul>
Environment	<p><b>Operating Temperatures:</b> 15°C to 28°C  <b>Relative Humidity:</b> 5% to 95% (non-condensing)  <b>Storage Temperature:</b> -40°C to 70°C  <b>BTU/HR:</b> &lt;400</p>	
Regulatory Information	<p>FCC Part 15, Subpart B Compliant          Foreign Trade Schedule B (2024): 8517.79.0000</p>	



\* The back panel pictured above features the coaxial return path configuration. Other configurations are available. Talk to an authorized Z-Band representative to learn more.